


TO.GO A Fig

ADVANCED ROLLING CODE TRANSMITTERS

2 and 4 channels







Training

Guide to memorisation of a TO.GO transmitter in a receiver or control unit. Watch the video.

- 2 or 4-channel transmitter of the TO.GO series with Advanced Rolling Code
- The new ARC coding guarantees maximum security due to the length of the transmitted code (128 bit) and the high number of possible combinations
- The TO.GO4A model allows users to set up to 9 channels, thanks to the option of activating the command by simultaneously pressing two buttons chosen by the user. This function allows avoiding accidental openings caused by pressing a button by mistake and is particularly indicated for use with alarm systems
- Equipped with 12 V battery for long lifespan
- Long range, up to 230 m in a free area
- Car accessory (TO.CLIP) or wall accessory (SMART) available



ONE.2WO

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



ONE.2WB

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, in box. 512 memorisable codes.



ONE.2WI

433.92 MHz receiver with power supply 12÷28 VDC / 21÷28 VAC, 2 channels with triple coding: Advanced Rolling Code and Rolling Code, plug-in. 512 memorisable codes.



ONE.4WB

4-channel receiver with full-range power supply (115-230 VAC/DC) and triple coding: Advanced Rolling Code, Rolling Code and Fixed Code, with outdoor IP54 box. 512 memorisable codes.



MEM2048

Additional memory for up to 2048 codes. For receivers of the ONE series.



AWO

433.92 MHz antenna for external installation with IP54 box, fitted with shielded RG58 5 m cable.







TO.GO2A

2-channels transmitter with Advanced Rolling Code. Easy insertion in the installations by reading QR code via the BeUP app, without having to go there.

TO.GO4A

4-channels transmitter with Advanced Rolling Code. Easy insertion in the installations by reading QR code via the BeUP app, without having to go there.





TO.GO2AS

2-channels transmitter with Advanced Rolling Code. Sequential coding for multiple insertions, also facilitated by reading QR code via the BeUP app, without having to go on the installation.

TO.GO4AS

4-channels transmitter with Advanced Rolling Code. Sequential coding for multiple insertions, also facilitated by reading QR code via the BeUP app, without having to go on the installation.



RG58 MT5 AWO antenna cable



AW

433.92 MHz stylus antenna for external installation, equipped with a shielded 3m RG58 cable.



AF.S

Column fixing bracket for STAR flashing light and AW antenna. The accessory can also be used for the antenna only.



SMART

Cover compatible with TO.GO transmitters for internal wall mounting.



TO.CLIP

Car accessory for TO.GO transmitters.



BT12

12 V Battery, for transmitter. Available in 50 pcs packing. www.beninca.com